

# MATERIAL SAFETY DATA SHEET


## SECTION 1 – MANUFACTURER INFORMATION

**Manufacturer/Distributor:** Super Source, Inc.  
906 Martin Luther King Dr.  
Thomasville, NC 27360  
336-475-1528  
**Revision Date:** 06/21/2007

**Emergency Phone:**  
INFOTRAC  
1-800-535-5053

**Trade Name/Synonyms:** **Blue Magic Tire Dressing**  
**Chemical Name/Synonyms:** N/A  
**Chemical Family:** Not Applicable  
**Formula:** Proprietary  
**Product Code:** N/A

## HAZARDOUS MATERIAL IDENTIFICATION SYSTEM:



**HAZARD RATING**  
4 = Extreme      3 = High  
2 = Moderate     1 = Slight  
0 = Insignificant   X = See Text

## SECTION 2 – HAZARDOUS INGREDIENTS

**Names of Hazardous Ingredients** See CFR29: 1910.1200 (i)-(13) Page 372

| <b>Chemical/Common Name:</b> | <b>Cas#</b> | <b>Percentage</b> | <b>PEL-OSHA</b> | <b>TLV ACGIH</b> |
|------------------------------|-------------|-------------------|-----------------|------------------|
| Mineral Spirits              | 8056-41-3   | >1                | 500PPM          | 100PPM           |

THIS PRODUCT DOES **NOT** CONTAIN REGULATED PRODUCTS OR PRODUCTS THAT ARE KNOWN TO CAUSE CANCER:  
(NTP, IARC, OSHA):

## SECTION 3 – HEALTH HAZARD DATA

### **Health Effects (Acute & Chronic):**

#### Acute:

- a) **Eyes:** Can cause severe irritation, redness, tearing, blurred vision.
- b) **Skin:** Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.
- c) **Inhalation:** Mild irritation.
- d) **Ingestion:** Can cause gastro-intestinal irritation, nausea, vomiting and diarrhea.

#### Chronic:

- a) **Inhalation** may increase susceptibility to respiratory illness.

**Primary Routes of Entry:** a) Skin                      b) Inhalation

**Medical Conditions Aggravated By Exposure:** Pre-existing skin, eye & respiratory disorders may be aggravated by exposure to product.

### **Emergency First Aid Procedures:**

- a) **Skin:** Immediately flush skin with lots of running water for at least 30 Minutes. Remove contaminated clothing & shoes. Wash before reuse.
- b) **Eyes:** Flush with large amounts of running water for at least 15 minutes. Consult Physician.
- c) **Inhalation:** If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet and get medical attention.
- d) **Ingestion:** *Do Not Induce Vomiting.* Call Physician Immediately. If conscious give lots of water or milk. Do not give anything by mouth to an unconscious or convulsing person.

# MATERIAL SAFETY DATA SHEET

Blue Magic Tire Dressing Continued

## SECTION 4 – CHEMICAL DATA

**Boiling Point (F):** >240 degrees **Specific Gravity (Water = 1):** 0.795  
**Vapor Pressure (mmHg):** < 2 **Percent Volatile By Volume (%):** > 85.00  
**Vapor Density (Air = 1):** 4.9 **Evaporation Rate (water =1)** 24  
**Solubility In Water:** Insoluble in Water  
**Appearance & Odor Information:** Thin Blue Liquid with a Fruity Odor.

## SECTION 5 – FIRE + PHYSICAL HAZARD DATA

**Flash Point (Method Used):** 108 degrees F T.C.C **Flammable Limits:** LEL = 0.9% UEL = 6%  
**Extinguishing Media:** Regular Foam, Waterfog, Carbon Dioxide, Dry Chemicals  
**Special Fire Fighting Procedures:** Clear fire area of unprotected personnel. Do not enter confined fire area without full bunker gear, including a positive breathing apparatus.  
**Unusual Fire and Explosion Hazards:** *Vapors are heavier than air and may travel the ground or be moved by ventilation and ignited by heat, pilot lights or other flames and ignition sources at a location distant from the material handling point. \* See Additional Comments.*  
**Incompatibility (Material to Avoid):** Avoid contact with strong oxidizing agents such as chlorine, permanganate, etc.  
**Hazardous Decomposition Products:** Burning may produce oxides of carbon and traces of hydrocarbons.  
**Hazardous Polymerization will not occur** **This Product is Stable**

## SECTION 6 – SPILL OR LEAK PROCEDURES

**Steps to be taken in case material is released or spilled:** Eliminate all ignition sources. Absorb on suitable absorbent & shovel into containers.  
**Waste disposal methods:** Contaminated absorbent may be disposed of according to local, state and federal regulations for products containing petroleum distillates.

## SECTION 7– EXPOSURE CONTROL INFORMATION

**Ventilation:**  
**Local Exhaust:** Below TLV(s) **Mechanical (General):** Explosion Proof  
**Special:** N/A **Other:** N/A  
**Respiratory Protection:** An appropriate NIOSH hydrocarbon canister or respirator for organic vapor is advised for proper environmental control.  
**Protective Gloves:** Wear resistant gloves such as nitrile rubber, PVC, etc.  
**Other Protective Equipment:** To prevent repeated and prolonged skin contact, wear impervious clothing & boots.  
**Other Engineering Controls:** Eye wash and quick drench facilities.  
**Work Practices:** Eye wash fountain and safety shower should be easily accessible. Discard properly such items as rags & trash soaked with product. Provide adequate ventilation.  
**Hygienic Practices:** Avoid contact with eyes, skin and clothing. Avoid inhalation of product vapors. Wash thoroughly after handling and before eating, drinking or smoking. Remove contaminated clothing promptly and wash thoroughly before reused.

## SECTION 8 – SPECIAL PRECAUTION

### **Precautions To Be Taken In Handling And Storage:**

- Protect from physical damage and keep tightly closed.
- Keep away from heat, sparks and open flames.
- Containers should be marked NA1993.
- Do not store under freezing conditions or above 120 degrees F
- Do not store near acids or acidic materials and oxidizers.

**Maintenance Precautions:** When working with FLAMMABLE material electrically ground all equipment and use only non-sparking tools.

### **Other Precautions:**

- Containers, even those that have been emptied will retain product residue and vapors. Always obey hazard warnings.
- Always ground metal containers while pouring.

### **Other Additional Comments:**

**\*Unusual Fire & Explosion Hazards:** a) Never use welding or cutting torch on or near container (even empty) because product (even residue) can ignite explosively. b) All 5-gallon pails and larger metal containers should be grounded when material is transferred.

Shipping Information: UN/NA #'s, Secondary Container Label Info Necessary or Suggested: Combustible Liquid NA1993 PG GP III  
No Labels Required. KEEP OUT OF THE REACH OR CHILDREN!